



SPECIFICATIONS:
 Voltage Rating: 250V AC Min
 Current Rating: 2.0A Min
 Dielectric Strength: 1000V AC For 1Minute
 Insulation Resistance: 1000Megohms Min
 Contact Resistance: 30Milliohms Max
 Operation Temperature: -55°C To + 125°C
 Product Withstanding Reflow Soldering:
 260°C For 15s
 Durability :5000 Cycles
 Normal Force At Working Position: 80g Min
 Insertion Force:>3N
 Insulator: High Temperature Thermoplastic
 UL 94V-0 Black (LCP Black)
 Contact: Beryllium Copper,
 Gold Flash Over Nickel

②	Terminal	—	3	Phosphor Bronze	Au Plated	—
①	Housing	—	1	LCP	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		 ELECTRONICS CO.,LTD			
DRAWN	xu qi feng	2014.12.05					
CHECKED				TITLE: 电池座			
APPROVALS				PART NO. BC-10-3PD			
TOLERANCES ARE		30~以下	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	
		10~30	±0.25				
		5~10	±0.20				
		~ 5	±0.15				
			±2'	DRAWING NO.		PROJ:	
ECN NO.	REV. A	DATE.	DESCRIPTION. NEW	CHANGE.	CHECK.	APPRO.	SHEET 1 OF 1