



**SPECIFICATIONS:**

Voltage Rating: 250V AC Min  
 Current Rating: 2.0A Min  
 Dielectric Strength: 1000V AC For 1Minute  
 Insulation Resistance: 1000Megohms Min  
 Contact Resistance: 30Milliohms Max  
 Operation Temperature: -55°C To + 125°C  
 Product Withstanding Reflow Soldering:  
 260°C For 15s

Durability :5000 Cycles  
 Normal Force At Working Position: 80g Min  
 Insertion Force:>3N  
 Insulator: High Temperature Thermoplastic  
 UL 94V-0 Black (LCP Black)  
 Contact: Beryllium Copper,  
 Gold Flash Over Nickel

②	Terminal	—	3	Phosphor Bronze	Au Plated	—
①	Housing	—	1	LCP	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		 ELECTRONICS CO.,LTD		
DRAWN	xu qi feng	2014.12.05				
CHECKED				PART NO.	BC-3-3P	
APPROVALS				TOLERANCES ARE	30~以上 ±0.30 10~30 ±0.25 5~10 ±0.20 ~ 5 ±0.15	
		ANGLE	UNIT: mm	SCALE: 1:1	PROJ:	
		±2'	DRAWING NO.	SHEET 1 OF 1		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			