



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:-20℃~70℃
 Operating force:3-20N
 Operating Life:5,000cycles

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.														
	A		NEW																	
<table border="1"> <tr> <td>①</td> <td>Terminal</td> <td>3</td> <td>Phosphor bronze</td> <td>Au Plating</td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>Housing</td> <td>1</td> <td>Nylon</td> <td>Black</td> <td></td> <td></td> </tr> </table>							①	Terminal	3	Phosphor bronze	Au Plating			②	Housing	1	Nylon	Black		
①	Terminal	3	Phosphor bronze	Au Plating																
②	Housing	1	Nylon	Black																
ITEM		PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK													
APPROVALS		DATE																		
DRAWN		J.X.Zhang	2013/11/11		TITLE: PHONE JACKES DC-085															
CHECKED																				
APPROVALS																				
TOLERANCES ARE		30~0.15	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ.													
		10~0.30	±0.20		DRAWING NO.		SHEET 1 OF 1													
		5~0.10	±0.15	±2'																
		~ 5	±0.10																	