



### PCB Layout

**SPECIFICATIONS:**  
 Voltage Rating: 250V AC Min  
 Current Rating: 2.0A Min  
 Dielectric Strength: 500V AC For 1Minute  
 Insulation Resistance: 1000Mmegohms Min  
 Contact Resistance: 30Milliohms Max  
 Operation Temperature: -55°C To +125°C  
 Product Withstanding Reflow Soldering:  
 260°C For 15s  
 Durability :5000 Cycles  
 Normal Force At Working Position: 80g Min  
 Packaging: 750pcs/Reel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Terminal	—	3	Phosphor Bronze	Au Plated	—
②	PIN-Strapped	—	2	Phosphor Bronze	Sn Plated	—
①	Housing	—	1	LCP	Black	—

APPROVALS		DATE	TITLE:	
DRAWN	JKUN.LU	2014.12.05	ELECTRONICS CO.,LTD	

CHECKED		TITLE:	
APPROVALS		PART NO.	BC-4-3PD

TOLERANCES ARE		ANGLE	UNIT:	SCALE:	DRAWING NO.	SHEET
30~ø以上	±0.30	±2°	mm	1:1		1 OF 1
10~30	±0.25					
5~10	±0.20					
~5	±0.15					

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			



電池座